

ACEA C3/C5 API SP ADDITIVE PACKAGE T3086

●Introduction

T3086 is formulated with various functional additives like good quality detergents, antioxidation & anti-wear additives, friction modifiers, etc. It shows excellent hardware protection and anti-wear performance. It can effectively reduce the formation of sludge, varnish, and carbon deposit in the engine. It can also reduce low speed pre ignition (LSPI).

●Recommended Treat Rate

Performance Level	Treat Rate (wt%)
ACEA C3/C5, API SP	11.5

●Specifications

Item	Typical Value	Test Method
Kinematic Viscosity (100°C), mm ² /s	Report	GB/T 265
Flash Point (COC), °C	>110	GB/T 3536
Magnesium, wt%	0.98	ASTM D5185 (ICP)
Zinc, wt%	0.66	ASTM D5185 (ICP)
Phosphorus, wt%	0.61	ASTM D5185 (ICP)
Boron, wt%	0.04	ASTM D5185 (ICP)
Molybdenum, wt%	0.02	ASTM D5185 (ICP)
Nitrogen, wt%	1.06	SH/T 0224
TBN, mgKOH/g	70	SH/T 0251

●Package, Handle & Storage

1. Packed in 200L metal drum, IBC-Tank or made to order.
2. Long term storage temperature should not exceed 45°C.
3. Handle & blending temperature should not exceed 65°C.
4. Not dangerous chemical, store in dry & clean warehouse.